

## 压敏电阻统一印字模版通知

通知日期：2021 年 7 月 16 日

通知方：台基防雷科技股份有限公司

受文方：所有客户


主题：压敏电阻统一印字模版

实施日期：2021 年 8 月 1 日起，现有生产库存品依照原印字标准至出清为止

### 通知内容

#### 1、通知主要内容

- 1.1 涉及型号：压敏电阻所有型号
- 1.2 变更原因：现有打印方式经长期因应安规升版或变动造成没有统一的模版。
- 1.3 工程分析：仅变更印字模版,符合安规印字要求,对组件其它电气特性与结构无影响。
- 1.4 印字模版：统一印字模版如下图所示。

05D~07D Series 以 GNR07D471K 为例	10D~20D Series 以 GNR20D471K 为例
	

### 产品印字编码内容

	<p>产品规格</p> <p>Date Code</p> <p>产线别</p>
安规打印	

#### 2、说明

- 2.1 当 UL 认证印字小于 7/32 英寸 ( 5.556mm ) 时或 CSA 认证印字小于 0.125 英寸 ( 3.175mm ) 时，若是注册商标符号®裸眼无法辨识时，可以省略注册商标符号® (如下方 UL 官方附件 1 与 CSA 官方附件 2)。
- 2.2 CSA 升版 MOV 认证后，印字右下角要求增加三角符号(如下方附件 3 CSA 证书首页)。

### 3. 附件

#### 3.1 附件 1

[marks.ul.com/about/ul-listing-and-classification-marks/downloadable-ul-marks/](https://marks.ul.com/about/ul-listing-and-classification-marks/downloadable-ul-marks/)

#### Marks and Labels

#### UL Listing and Classification Marks

Appearance and Significance

UL Marketing Guidelines

#### UL Mark Artwork

Hologram UL Marks

Labels

Designing and Ordering UL Marks

## UL Mark Artwork

Congratulations on successfully completing your UL certification and earning the UL Mark! Here you will find many of the artwork files that you will need to create your UL certification label featuring our Marks, including camera-ready artwork of the UL Listed, UL Classified and UL Recognized Component Marks. As you are creating your UL certification label, please keep the following in mind:

- Always use the authorized artwork files provided here for you to download. Do not recreate any UL Mark or any elements of the UL Mark. If you are using the enhanced Mark or promotional badge, please visit the Marks Hub to obtain authorized artwork files.
- Unless otherwise designated for a specific Mark, the UL Mark itself may only be displayed in black on a light background, white on a dark background or red (PMS 200 or equivalent). For the UL Listed, UL Classified and UL Recognized Component Marks, the UL-in-a-circle and the backward UR — including any text immediately above or below the UL-in-a-circle and backward UR — and any required country identifiers must be displayed in a single color (black, white or red). No other colors are acceptable. Other required elements for UL Listed and UL Classified certification Marks such as product identity, control number or file number may be displayed in black on a light background or white on a dark background.
- The minimum height of the registered trademark symbol ® in all variations of the UL Listed, UL Classified and UL Recognized Component Marks must be at least 3/64 of an inch. When the overall diameter of the UL Listed or UL Classified Mark is less than 3/8 of an inch, the trademark symbol may be omitted if it is not legible. When the overall height of the UL Recognized Component Mark is less than 7/32 of an inch, the trademark symbol may be omitted if it is not legible.
- The font for all letter forms comprising all variations of the UL Listed and UL Classified Marks is Helvetica Condensed Black. Although not required, please feel free to utilize this font for other required UL certification information such as the product identity, company name, file number or control number.
- An important benefit of your UL certification is the ability to use the UL Mark you have earned in your advertising and promotion. Please visit our [marketing guidelines](#) for additional information about how to market using your UL certification and the UL Mark.

#### 3.2 附件 2 : CSA MARKS GUIDELINES DQD512-02

##### 2. SIZE CATEGORIES AND MINIMUM SIZE

The CSA International monogram marks have been grouped into small, medium and large size categories to allow the registration symbol ® to print legibly but not dominate the mark when used within the specified size range. For applications where the height of the “C” in the monogram is less than one quarter of an inch but greater than the minimum size of one eighth of an inch (0.125”-0.250”), use the small versions of the mark. For applications where the height of the “C” in the monogram is greater than one quarter of an inch but less than five eighths of an inch (0.250”-0.625”), use the medium versions of the mark. For applications where the height of the “C” in the monogram is greater than five eighths of an inch (0.625”), use the large versions of the mark.

When the height of the “C” in the monogram is less than one eighth of an inch (0.125”) the registration symbol ® may be omitted if it is not legible to the naked eye.





3.3 附件 3 : CSA 证书首页






# Certificate of Compliance

Certificate:	1278211	Master Contract:	163001
Project:	70202546	Date Issued:	2019-05-02
Issued to:	Ceramate Technical Co., Ltd. 1F No. 4, Ln. 311, Sec. 1 Jieshou Rd. New Taipei City, 237 TAIWAN		

*The products listed below are eligible to bear the CSA Mark shown with adjacent indicator ▲*



Issued by: *Silby John*  
Silby John

核准		审核		制表	
----	---	----	---	----	---