






Comtector
半导体放电管

系列 Type series	CxxxxD	CxxxxA	CxxxxB	CxxxxE	
封装型式 Package	TO-92	SMA	SMB	DO-15	DO-27
外表尺寸 Dimensions ØD x H L x W x H (mm)	L x W x H	L x W x H	L x W x H	ØD x H	
	4.6 x 3.6 x 4.7	4.3 x 2.6 x 2.2	4.4 x 3.6 x 2.3	Ø3.2 x 6.6	Ø5.3 x 9.0
					
Part Number					
0080	⊙	⊙	⊙	⊙	⊙
0300	⊙	⊙	⊙	⊙	⊙
0640	⊙	⊙	⊙	⊙	⊙
0720		⊙	⊙	⊙	⊙
0900	⊙	⊙	⊙	⊙	⊙
1100	⊙	⊙	⊙	⊙	⊙
1300	⊙	⊙	⊙	⊙	⊙
1500	⊙	⊙	⊙	⊙	⊙
1800	⊙	⊙	⊙	⊙	⊙
2000				⊙	⊙
2300	⊙	⊙	⊙	⊙	⊙
2600	⊙	⊙	⊙	⊙	⊙
3100	⊙	⊙	⊙	⊙	⊙
3500	⊙	⊙	⊙	⊙	⊙
4000	⊙	⊙	⊙	⊙	⊙
4500				⊙	⊙
5000				⊙	⊙
8000			⊙		

Surge Rating (Ipp)1 表

*	2 X 10µs (A)	8 X 20µs (A)	10 X 160µs (A)	10 X 560µs (A)	10 X 1000µs (A)
A	150	150	90	50	50
B	250	250	150	100	80
C	500	400	200	150	100

V-I 特性图

