





Transient Voltage Suppressor – Surface Mount Series
瞬态电压抑制器 – 贴片式系列

型号 Type	SMF	SMA	P4SMAJ	SMB	P6SMBJ	SMC	1.5SMCJ
额定功率 (W)	200W	400W	400W	600W	600W	1500W	1500W
封装型式 Package	SOD123FL	SMA / DO-214AC	SMA / DO-214AC	SMB / DO-214AA	SMB / DO-214AA	SMC / DO-214AB	SMB / DO-214AA
外表尺寸 Dimensions L x W x H (mm)	2.8 x 1.8 x 1 	4.4 x 2.6 x 2.4	4.4 x 2.6 x 2.4	4.4 x 3.6 x 2.3 	4.4 x 3.6 x 2.3	6.9 x 5.9 x 2.3	6.9 x 5.9 x 2.3
Part Number							
5.0	⊙	⊙		⊙		⊙	
6.0	⊙	⊙		⊙		⊙	
6.5	⊙	⊙		⊙		⊙	
6.8			⊙		⊙		⊙
7.0	⊙	⊙		⊙		⊙	
7.5	⊙	⊙	⊙	⊙	⊙		⊙
8.0	⊙	⊙		⊙		⊙	
8.2			⊙		⊙		⊙
8.5	⊙	⊙		⊙		⊙	
9.0	⊙	⊙		⊙		⊙	
9.1			⊙		⊙		⊙
10.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
11.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
12.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
13.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
14.0	⊙	⊙		⊙		⊙	
15.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
16.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
17.0	⊙	⊙		⊙		⊙	
18.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
19.0	⊙						
20.0		⊙	⊙	⊙	⊙	⊙	⊙
22.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
24.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
26.0	⊙	⊙		⊙		⊙	
27.0			⊙		⊙		⊙
28.0	⊙	⊙		⊙		⊙	
30.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
33.0	⊙	⊙		⊙		⊙	
36.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
39.0			⊙		⊙		⊙
40.0	⊙	⊙		⊙		⊙	
43.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
45.0	⊙	⊙		⊙		⊙	
47.0			⊙		⊙		⊙
48.0	⊙	⊙		⊙		⊙	
51.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
54.0	⊙	⊙		⊙		⊙	
56.0			⊙		⊙		⊙
58.0	⊙	⊙		⊙		⊙	
60.0	⊙	⊙		⊙		⊙	
62.0			⊙		⊙		⊙
64.0	⊙	⊙		⊙		⊙	
68.0			⊙		⊙		⊙
70.0	⊙	⊙		⊙		⊙	
75.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
78.0	⊙	⊙		⊙		⊙	
80.0	⊙						
82.0			⊙		⊙		⊙
85.0	⊙	⊙		⊙		⊙	
90.0	⊙	⊙		⊙		⊙	
91.0			⊙		⊙		⊙
100.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
110.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
120.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
130.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
140.0	⊙						
150.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
160.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
170.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
180.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
190.0	⊙						
200.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙
220.0	⊙	⊙	⊙	⊙	⊙	⊙	⊙



Transient Voltage Suppressor – Surface Mount Series
瞬态电压抑制器– 贴片式系列

型号 Type	SMF	SMA	P4SMAJ	SMB	P6SMBJ	SMC	1.5SMCJ
额定功率 (W)	200W	400W	400W	600W	600W	1500W	1500W
封装型式 Package	SOD123FL	SMA / DO-214AC	SMA / DO-214AC	SMB / DO-214AA	SMB / DO-214AA	SMC / DO-214AB	SMB / DO-214AA
外表尺寸 Dimensions L x W x H (mm)	2.8 x 1.8 x 1	4.4 x 2.6 x 2.4	4.4 x 2.6 x 2.4	4.4 x 3.6 x 2.3	4.4 x 3.6 x 2.3	6.9 x 5.9 x 2.3	6.9 x 5.9 x 2.3
Part Number							
250.0		⊙	⊙	⊙	⊙	⊙	⊙
300.0		⊙	⊙	⊙	⊙	⊙	⊙
350.0		⊙	⊙	⊙	⊙	⊙	⊙
400.0		⊙	⊙	⊙	⊙	⊙	⊙
440.0		⊙	⊙	⊙	⊙	⊙	⊙
480.0			⊙		⊙		⊙
510.0			⊙		⊙		⊙
530.0			⊙		⊙		⊙
540.0			⊙		⊙		⊙
550.0			⊙		⊙		⊙

Transient Voltage Suppressor – Surface Mount Series
瞬态电压抑制器– 贴片式系列

型号 Type	SMD	5KSMD	型号 Type	SMD	5KSMD
额定功率 (W)	3000W	5000W	额定功率 (W)	3000W	5000W
封装型式 Package	SMC / DO-214AB	SMC / DO-214AB	封装型式 Package	SMC / DO-214AB	SMC / DO-214AB
外表尺寸 Dimensions L x W x H (mm)	6.9 x 5.9 x 2.3				
Part Number			Part Number		
5.0	⊙		43.0	⊙	⊙
6.0	⊙		45.0	⊙	⊙
6.5	⊙		47.0		
6.8			48.0	⊙	⊙
7.0	⊙		51.0	⊙	⊙
7.5	⊙		54.0	⊙	⊙
8.0	⊙		56.0		
8.2			58.0	⊙	⊙
8.5	⊙		60.0	⊙	⊙
9.0	⊙		62.0		
9.1			64.0	⊙	⊙
10.0	⊙		68.0		
11.0	⊙		70.0	⊙	⊙
12.0	⊙	⊙	75.0	⊙	⊙
13.0	⊙	⊙	78.0	⊙	⊙
14.0	⊙	⊙	80.0		
15.0	⊙	⊙	82.0		
16.0	⊙	⊙	85.0	⊙	⊙
17.0	⊙	⊙	90.0	⊙	⊙
18.0	⊙	⊙	91.0		
19.0			100.0	⊙	⊙
20.0	⊙	⊙	110.0	⊙	⊙
22.0	⊙	⊙	120.0	⊙	⊙
24.0	⊙	⊙	130.0	⊙	⊙
26.0	⊙	⊙	140.0		
27.0			150.0	⊙	⊙
28.0	⊙	⊙	160.0	⊙	⊙
30.0	⊙	⊙	170.0	⊙	⊙
33.0	⊙	⊙	180.0	⊙	
36.0	⊙	⊙	190.0		
39.0			200.0	⊙	
40.0	⊙	⊙	220.0	⊙	

Transient Voltage Suppressor – Axial Lead Series



瞬态电压抑制器- 插件式系列											
型号 Type	P4KE	P6KE	1.5KE	3KP	5KP	型号 Type	P4KE	P6KE	1.5KE	3KP	5KP
额定功率 (W)	400W	600W	1500W	3000W	5000W	额定功率 (W)	400W	600W	1500W	3000W	5000W
封装型式 Package	DO-41	DO-15	DO-201AE	R6	R6	封装型式 Package	DO-41	DO-15	DO-201AE	R6	R6
外型尺寸 Dimensions ØD ×H (mm)	2.4Ø x 4.7	3.1Ø x 6.7	5.2 Ø x 8.4	8.9 Ø x 8.9	8.9 Ø x 8.9	外型尺寸 Dimensions ØD ×H (mm)	2.4Ø x 4.7	3.1Ø x 6.7	5.2 Ø x 8.4	8.9 Ø x 8.9	8.9 Ø x 8.9
Part Number						Part Number					
5.0				⊙	⊙	54.0				⊙	⊙
6.0				⊙	⊙	56.0	⊙	⊙	⊙		
6.5				⊙	⊙	58.0				⊙	⊙
6.8	⊙	⊙	⊙			60.0				⊙	⊙
7.0				⊙	⊙	62.0	⊙	⊙	⊙		
7.5	⊙	⊙	⊙	⊙	⊙	64.0				⊙	⊙
8.0				⊙	⊙	68.0	⊙	⊙	⊙		
8.2	⊙	⊙	⊙			70.0				⊙	⊙
8.5				⊙	⊙	75.0	⊙	⊙	⊙	⊙	⊙
9.0				⊙	⊙	78.0				⊙	⊙
9.1	⊙	⊙	⊙			82.0	⊙	⊙	⊙		
10.0	⊙	⊙	⊙	⊙	⊙	85.0				⊙	⊙
11.0	⊙	⊙	⊙	⊙	⊙	90.0				⊙	⊙
12.0	⊙	⊙	⊙	⊙	⊙	91.0	⊙	⊙	⊙		
13.0	⊙	⊙	⊙	⊙	⊙	100.0	⊙	⊙	⊙	⊙	⊙
14.0				⊙	⊙	110.0	⊙	⊙	⊙	⊙	⊙
15.0	⊙	⊙	⊙	⊙	⊙	120.0	⊙	⊙	⊙	⊙	⊙
16.0	⊙	⊙	⊙	⊙	⊙	130.0	⊙	⊙	⊙	⊙	⊙
17.0				⊙	⊙	150.0	⊙	⊙	⊙	⊙	⊙
18.0	⊙	⊙	⊙	⊙	⊙	160.0	⊙	⊙	⊙	⊙	⊙
20.0	⊙	⊙	⊙	⊙	⊙	170.0	⊙	⊙	⊙	⊙	⊙
22.0	⊙	⊙	⊙	⊙	⊙	180.0	⊙	⊙	⊙	⊙	⊙
24.0	⊙	⊙	⊙	⊙	⊙	200.0	⊙	⊙	⊙	⊙	⊙
26.0				⊙	⊙	210.0				⊙	⊙
27.0	⊙	⊙	⊙			220.0	⊙	⊙	⊙	⊙	⊙
28.0				⊙	⊙	250.0	⊙	⊙	⊙		⊙
30.0	⊙	⊙	⊙	⊙	⊙	300.0	⊙	⊙	⊙		
33.0	⊙	⊙	⊙	⊙	⊙	350.0	⊙	⊙	⊙		
36.0	⊙	⊙	⊙	⊙	⊙	400.0	⊙	⊙	⊙		
39.0	⊙	⊙	⊙			440.0	⊙	⊙	⊙		
40.0				⊙	⊙	480.0	⊙	⊙	⊙		
43.0	⊙	⊙	⊙	⊙	⊙	510.0	⊙	⊙	⊙		
45.0				⊙	⊙	530.0	⊙	⊙	⊙		
47.0	⊙	⊙	⊙			540.0	⊙	⊙	⊙		
48.0				⊙	⊙	550.0	⊙	⊙	⊙		
51.0	⊙	⊙	⊙	⊙	⊙	600.0		⊙			